

## DIGITAL CONTACT-NON CONTACT TACHOMETER DT2236C

**APPLICATION:** This is a Contact & Non-Contact Digital Tachometer with Wide Measuring Range and High Resolution.

### FEATURES:

- Display 5 Digital LCD Display
- Memory: Max Value, Min Value, Last Value.
- Detecting Distance: 2 to 20 inches. (for non-contact type)
- The Last Value/ Max Value/ Min Value will be Automatically Stored in Memory.
- Low Battery Indication.
- Power Supply: 4 X 1.5-volt AA Size Batteries □ Display Size: 42 X 22 mm.
- Unit Size: 215 X 65 X 38 mm.
- Weight: 300 gms Including Batteries
- Accessories: Operational Manual, Carrying Case, 2pcs Reflecting Tape Marks (202mm each), Speed Measurement Fitting, RPM Measurement Fitting.



### SPECIFICATION:

- Testing Range Contact: 0.5 To 19999 RPM
- Non-Contact 2.5 to 99999 RPM (r/min)  
Surface Speed: 1) 0.05 to 1999.9 m/min □ Resolution: Contact:  
RPM :0.1RPM (up to 0.05 TO 1999.9 RPM)  
1RPM (OVER 1000 RPM)  
Surface Speed: 0.01 m/min (0.5 to 99.99m/min)  
m/min (over 100 m/min)
- Non-Contact: 0.1RPM (2.5 TO 999.9 RPM)  
1RPM (OVER 1000 RPM)
- Accuracy ±0.05%
- Testing Parameters: RPM, m/min, ft/min
- Sampling Time: 0.8 sec (over 60 RPM)
- Operation Temperature: 0°C to 50°C