

7250IN

Features:

- Polarization Index (PI)
- Dielectric Absorption (DAR)
- USB Interface
- Over Range Warning
- High Voltage Indication



DC VOLTAGE

Range	Resolution	Accuracy
±30~± 600V	1V	±2.0% of rdg + 3 digits

AC VOLTAGE

Range	Resolution	Accuracy
30-600V (50/60Hz)	1V	±2.0% of rdg + 3 digits

INSULATION RESISTANCE MEASUREMENT

Output Voltage	Display Range	Open Circuit Voltage	Test Current	Accuracy	Short Circuit
500V	0.0MΩ~20GΩ	DC 500V 0% - +20%	1mA-1.2mA @ 500KΩ	0.0-99.9MΩ ± 3% of rdg + 5 digits	Maximum than 2.0mA
				100MΩ-9.99GΩ ± 5% of rdg + 5 digits	
				10.0-20.0GΩ ± 10% of rdg + 5 digits	
1000V	0.0MΩ~40GΩ	DC 1000V 0% - +20%	1mA-1.2mA @ 1MΩ	0.0-99.9MΩ ± 3% of rdg + 5 digits	Maximum than 2.0mA
				100MΩ-9.99GΩ ± 5% of rdg + 5 digits	
				10.0-40.0GΩ ± 10% of rdg + 5 digits	
2500V	0.0MΩ~100GΩ	DC 2500V 0% - +20%	1mA-1.2mA @ 2.5MΩ	0.0-99.9MΩ ± 3% of rdg + 5 digits	Maximum than 2.0mA
				100MΩ-9.99GΩ ± 5% of rdg + 5 digits	
				10.0-100GΩ ± 10% of rdg + 5 digits	
5000V	0.0MΩ~1000GΩ	DC 5000V 0% - +20%	1mA-1.2mA @ 5MΩ	0.0-99.9MΩ ± 3% of rdg + 5 digits	Maximum than 2.0mA
				100MΩ-9.99GΩ ± 5% of rdg + 5 digits	
				10.0-99.9GΩ ± 10% of rdg + 5 digits	

POWER

AA 1.5V X 8

- Standard Accessories : Test Lead, USB Cable & Software, Power Adaptor
- Dimension : 505(H) x 345(W) x 345(D)mm