

**TECHNICAL DATA** 

## Fluke 59 Mini Infrared Thermometer



# **Key features**

- Small in size easily fit in your pocket
- Laser targeting for fast, precise measurements
- Backlit display for easy reading in dark work areas
- 8:1 distance to spot ratios measures a 10 cm spot from 10 meters to target just what you want
- ± 2% basic accuracy gives you readings you can trust

#### **Product overview: Fluke 59 Mini Infrared Thermometer**

The Fluke 59 Mini Infrared Thermometer is the perfect combination of small size and big capability. With laserprecision targeting and 2% basic accuracy, the Fluke 59 Mini IR Thermometer enables professionals to diagnose heating and ventilation problems and monitor the temperature of electrical motors and electrical panels without contact. The 59 Mini puts quick, reliable temperature checks at your fingertips.

### **Specifications: Fluke 59 Mini Infrared Thermometer**

Specifications	
Measurement range	u2013 18u00b0C to 275u00b0C (0u00b0F to 525u00b0F)



Accuracy	100u00b0C - 275u00b0C (212u00b0F to 515u00b0F):	u00b12% of reading		
	0u00b0C - 100u00b0C (32u00b0F to 212u00b0F):	u00b12u00b0C(3.5u00b0F) of reading		
	Below 0u00b0F (32u00b0F):	u00b13u00b0C(5.5u00b0F) of reading		
Repeatability	u00b11% of reading or u00b11u00b0C whichever is greater			
Emissivity	Pre-set 0.95	Pre-set 0.95		
Distance-to-spot size	8:1 calculated @ 90% energy	8:1 calculated @ 90% energy		
Response time	< 500ms	< 500ms		
Display resolution	0.2u00b0C (0.5u00b0F)	0.2u00b0C (0.5u00b0F)		
Spectral range	6.5 u2013 18 um thermopile detector			
Display hold 7 seconds	Yes			
LCD backlight	Yes			
Temperature display	u00b0C or u00b0F selectable			
Low baery indicator	Yes			
Ambient operating range	0u00b0C - 50u00b0C (32u00b0F to 120u00b0F)			
Relative humidity	10% - 90% RH non-condensing @ up to 30u00b0C(86u00b0F)			
Storage temperature	-20u00b0C - 65u00b0C(-4u00b0F to 150u00b0F) without baery			
Power	9V baery included			
Baery life	4 hours			
Weight	200g, with baery			
Dimensions (H x L x W)	152mm x 102mm x 38mm	152mm x 102mm x 38mm		
Standards	Conforms to EN 61326-1 electromagn	Conforms to EN 61326-1 electromagnetic		
	Emissions and susceptibility	Emissions and susceptibility		
	EN 61010-1 General safety	EN 61010-1 General safety		
	EN 60825-1 Laser safety	EN 60825-1 Laser safety		
Certification	CE, CMC	CE, CMC		
Warranty	1 year			



# **Ordering information**



#### FLUKE-59

Fluke 59 Mini Infrared Thermometer

Fluke 59 includes:

- Battery
- Quick Start Guide



#### Fluke. Keeping your world up and running.®

Fluke Corporation

PO Box 9090, Everett, WA 98206 U.S.A.

For more information call: In the U.S.A. (800) 443-5853 In Canada (800) 36-FLUKE

From other countries +1 (425) 446-5500

www.fluke.com

©2024 Fluke Corporation.

Specifications subject to change without notice.

11/2024

Modification of this document is not permitted without written permission from Fluke Corporation.