



An ISO 9001:2015 Company

CONTACT TYPE DIGITAL TACHOMETER MODEL KM 2235B



Adaptor for liner Surface



Adaptor for round shaft with "V" groove.



Adaptor for round shaft with "V" groove.

KUSAM-MECO Digital Tachometers use latest technology for accurate measurements. It has Exclusive one chip of Microcomputer LSI Circuit, It is housed in tough ABS case & has ergonomic design for easy holding in the hand.

SPECIFICATIONS :

Display	5 digits, 18mm (0.7") LCD White Backlight display
Sampling Time	0.8 sec. (Over 60 RPM)
Test Range	Autoranging
Range I	0.5-999.9 RPM
Range II	1000-19,999 RPM
Speed	0.05 ~ 1999.9 m/min
Length	0.05 ~ 99999 m
Accuracy	± (0.05% + 1dgt)
Resolution	0.1 RPM (0.5-999.9 RPM)
	1 RPM (over 1000RPM)
Memory	Max value, Min value & Last value automatically stored in memory & save 96 set of continuous data.
Operating Temperature	0 - 50°C
Operating Humidity	Less than 80% RH
Power Consumption	Approx. 65mA
Power Supply	4 x 1.5V AA Battery or to external DC 6V Regulated power supply.
Dimension (L X W X D)	155 x 70 x 35 mm
Weight	235 gms including batteries
Accessories	User Manual, Carrying case, Surface speed Test Wheel, RPM adapter(cone) & (funnel).
Optional Accessories	AC Adaptor

All Specifications are subject to change without prior notice.



G-17, Bharat Industrial Estate, T. J. Road, Sewree (W), Mumbai - 400 015. INDIA.
Tel. : 022-24156638, 27754546, 24124540, 24181649, 27750662, 27750292
Email : sales@kusam-meco.co.in Website : www.kusamelectrical.com