



FEATURES :

- ☒ LARGE COLOUR LCD DISPLAY & BACKLIGHT
- ☒ DATA HOLD
- ☒ °C OR °F SELECTION
- ☒ HIGHLY ACCURATE & NON-CONTACT MEASUREMENT
- ☒ SIMPLE TO USE
- ☒ TEMPERATURE ALARM
- ☒ CIRCULAR LASER POINTER INCREASE THE TARGET ACCURACY



Back light



Temp



Low Battery Indication



Laser Warning

TECHNICAL DATA :

RANGE	-50°C~580°C / -58°F~1076°F
ACCURACY	-50°C~0°C / -4°F~32°F:±4°C/7°F above 0°C/32°F:±2% of reading ±2°C/3.6°F
RESOLUTION	0.1°C~0.1°F
DISTANCE SPOT RATIO	13:1
EMITTANCE	ADJUSTABLE FROM 0.01~1.0
RESPONSE TIME	<500ms
RESPONSE SPECTRUM	8~14um
DIODE LASER	OUTPUT <1mW/630~670nm Level 2(II) Laser
AUTO POWER OFF	AROUND 20 SECOND
RELATIVE HUMIDITY	OPERATING : 10 TO 95% RH

POWER : 1.5V X 2 AAA BATTERY

Dimension	: H156 x W99 x D28 mm
Weight	: Approx. 176 Gms.
Accessories	: Soft Carry Case, User Manual & Battery
Qty	: 40 Pcs. in a Box.