MOISTURE METER

Model: PMS-713 *ISO-9001, CE, IEC1010*





MOISTURE METER

Model: PMS-713

FEATURES			
*	Designed to check the moisture level of wood, concrete, and other		
	non-wood material.		
*	6 % to 40 % moisture range on wood.		
*	0 to 100% relative moisture value for Concrete and other non-wood		
	material.		
*	All in one, meter build in the test pins.		
*	Data hold function to freeze the desired value on display.		
*	Microprocessor circuit ensures high accuracy and provides special		
	functions and features.		
*	Operates from DC 1.5V (UM4/AAA) x 4 PCs batteries.		
*	Built-in low battery indicator.		
*	With the pins' protection cover.		
*	Durable, long-lasting components, enclosed in strong, compact		
	ARS-plastic housing		

SPECIFICATIONS		
Applications	Designed to check the moisture level of wood,	
	concrete and other non-wood material.	
Measuring	Used the 2 pins electrode to measure the conductive	
Principal	ability of the species, then converter to the reading	
	of % " Moisture of Content ".	
Display	LCD size: 28 mm x 19 mm.	
Material/ Range	Material 1: 0 to 100% relative moisture value for	
	Concrete. and other non-wood material.	
	Material 2: 6% to 40% moisture range on wood.	
Resolution	0.1 %.	
Accuracy	± (5 % + 5 d)	
	@ 23± 5 ℃	
	@ Material 1 : 13 % to 100%	
	@ Material 2 : 6 % to 40%	
Circuit	Custom one-chip of microprocessor LSI circuit.	
Probe	2 pins moisture electrode.	
Data Hold	Freeze the display reading.	
Sampling Time	Approx. 0.8 second.	
Operating Temp.	0 to 50 ℃.	
Operating Humidity	Less than 80% R.H.	
Power Supply	DC 1.5 V battery (UM4/AAA) x 4 PCs,	
Power Current	Approx. DC 12 mA	
Weight	180 g/ 0.40 LB. @ Battery is included.	
Dimension	180 x 40 x 40 mm (7.1" x 1.6" x 1.6")	
Accessories	Instruction manual1 PC.	
Included	Extra test pins1 Set.	
Optional	* Soft carrying case with sash	
Accessory	(210 x 80 x 50 mm), Model : CA-52A	
	* Test pins , MP-02	

^{*} Appearance and specifications listed in this brochure are subject to change without notice. 0705-PMS713