



BATTERY TESTER BFT225

<u>APPLICATION</u>: The battery tester is used for lead-acid starting battery along with checking conditions of the battery starting up, charging & loading. The Tester gives the reading by a large LCD and hints by sound and light when testing.

FEATURES:

- With great design, easy operation, precise reading, complete functions, this tester supplies the readings by a large LCD and hints by sound and light when testing.
- Battery Voltage, Battery Capacity
- Cold Start Current
- Internal Resistance
- State Health, State Charge
- Vehicle Starting Load Voltage Test (START-LOAD)
- Battery Maximum Load Voltage Test (RUN-LOAD)
- Vehicle to Battery charging Voltage Test (CHARGE-SYS)
- Supports AGM/EFB battery start-stop test
- CAT II 300V
- Voltage range 8V- 36V
- Quick Test → 3Ah-2000Ah
- Support variety of Battery Specifications: CCA, IEC, SAE, EN, DIN, JIS.
- Operating Temperature : -10 ~ 50°C
- Accessories: Instruction Manual.
- Dimension: 90X60X33mm
- Weight : 286g

MEXTECH BFT225 Type * Semil Cod. GEL. EFS OF Life 188% Reglace Peor Charge Regulate to the Management of the Manageme

SPECIFICATION:

Working Voltage 12V/24V(lead-acid storage batteries, should not be used for battery testing) Accurate Test:

Standard	Description	Range
CCA	Cold Starting Current	100 ~1700
IEC	International	100 ~1000
	Electrotechnical	
	Commisssion	
	Standard	
DEN	European Industrial	100 ~1700
	Standard	
DIN	German Industrial	100 ~1000
	Standard	

JIS → Need to compare CCA with the Table